



Fiber Optic Network LIU - Wall Mount

The Western Wall/Pole Mount LIU is enclosure that provides cross-connect and inter connect capabilities for splicing and terminating outdoor cables & FTTH drop cables in fiber access network. It integrates three main functions of fiber splicing, cable winding & storing, and interface management.

FEATURES

- ▶ Suitable for interconnect in cables distribution or cables and optical equipment's.
- ▶ Space saving with its compact & small design of enclosure.
- ▶ Wall/pole mount for outdoor application with IP55 Rating an manage both splices and terminations.
- ▶ Can include adapter panels for maximum 24 ports LC/SC/ST/FC terminations.
- ▶ Splice tray/splice bridge to protect the fibers.

SPECIFICATION

PARTS	MATERIAL	DIMENSIONS
Body	CRCA steel,1.0mm	320Wx400Hx62D
Cover	CRCA steel,1.2mm	320Wx400Hx20D
Adapter Panel	Cold Steel, 1.5mm	Depend on port count
Cable Entry	Plastic	PG16 & PG 21
Wall Mounting Bracket	CRCA steel,2.0mm	300Wx50H
Max Port Count	24F	
ORDERING INFORMATION		
WTN-LU-06-WM	LIU 6 Port Wall Mount - Loaded (LC Simplex) - Single Mode	
WTN-LU-12-WM	LIU 12 Port Wall Mount - Loaded (LC Simplex) - Single Mode	
WTN-LU-24-WM	LIU 24 PORT Wall Mount - Loaded (LC Duplex) - Single Mode	